

— 16-KEY BLF CONSOLE / 4.3" COLOUR LCD EXPANSION MODULE

ATCOM AET

The ATCOM AET is a 16-key BLF expansion console with a 4.3" colour LCD display, designed for use with ATCOM A41, A41W, A48, A48W, A48WAC, A68, A68W, and A68WAC IP phones. It displays subscriber status and photographs directly on-screen, with support for up to 5 AET consoles connected to a single phone.

16 BLF Keys | 4.3" Colour LCD | 480×272 Display | Up to 5 per Phone



UNIT — ATCOM AET

01 OVERVIEW

The ATCOM AET expansion console is compatible with ATCOM A41x, A48x, and A68x series phones. Equipped with a 4.3" colour LCD (480×272), it displays the status and photographs of registered contacts (pre-loaded into the phonebook or synchronized via LDAP). A tri-colour LED on each key provides instant visual status indication. The AET is powered directly by the host phone and configured through its own independent Web interface, making it ideal for receptionists, call center agents, and executive assistants who need fast access to multiple contact lines.

02 WHY CHOOSE ATCOM AET

WHY/01 Colour Contact Display

4.3" colour LCD (480×272) shows subscriber name, photo, and status at a glance — no need to memorize extension numbers.

WHY/02 Scrollable Contact List

Browse all registered contacts directly on the console screen, supporting up to 44 programmable actions across 16 keys.

WHY/03 Tri-Colour LED per Key

Each of the 16 programmable keys features a three-colour LED for immediate visual status indication (available, busy, ringing).

WHY/04 Phone-Powered Design

Draws power directly from the connected phone — no external adapter required, reducing cable clutter on the desk.

WHY/05 Independent Web Interface

Configure all BLF keys, labels, and settings via the AET's own dedicated web interface without touching the host phone.

03 KEY FEATURES

◆ 16 programmable BLF keys	◆ Up to 44 programmable actions
◆ 4.3" colour LCD, 480×272 resolution	◆ Tri-colour LED on every key
◆ Contact name, photo & status display	◆ Scrollable contact list
◆ Powered by host phone (no adapter)	◆ Up to 5 consoles per phone
◆ 2-port Ethernet switch per module (LAN/PC)	◆ LDAP photo synchronization
◆ Independent Web configuration interface	◆ Compatible: A41x, A48x, A68x series

04 TECHNICAL SPECIFICATION

DISPLAY		DISP
SCREEN	4.3" TFT colour LCD	
RESOLUTION	480 × 272 pixels	
INFO SHOWN	Subscriber name, photo, call status	
KEYS & LEDS		KEY
PROG KEYS	16 programmable BLF keys	
ACTIONS	Up to 44 programmable actions	
LED	Tri-colour LED per key (available / busy / ringing)	
CONNECTIVITY		CONN
ETHERNET	2-port switch per module — 10/100TX (LAN, PC)	
EXPANSION	Up to 5 AET consoles per host phone	
COMPATIBLE	ATCOM A41, A41W, A48, A48W, A48WAC, A68, A68W, A68WAC	
CONTACTS & INTEGRATION		CONTACTS
PHONEBOOK	Photo display from phonebook or LDAP sync	
NAVIGATION	Scrollable contact list on console screen	
MANAGEMENT		MGT
CONFIG	Independent Web interface per console	
MAC SETUP	Enter console MAC address in phone's web UI to activate	
PHYSICAL		PHY
POWER	5V, 2A supply (included) / powered from host phone	
STORAGE TEMP	-40 – +70 °C	
OPERATING TEMP	-10 – +50 °C	
HUMIDITY	10 – 95%	
PKG DIMENSIONS	150 × 210 × 140 mm	